



400G Duplex Multimode 50/125 OM4 Fiber Optic Cable (CS-PC/CS-PC), Round LSZH Jacket, Magenta, 3 m

MODEL NUMBER: N822C-03M-MG





400 GbE Ethernet cable supports high bandwidths necessary for next-generation cloud services, hyperscale data centers and telecom carriers.

Features

400 GbE Cable Supports Higher Bandwidths Needed for Next-Gen Data Networking

As the amount of traffic in data networks grows, so does the need for next-generation devices and fiber cables to support much higher bandwidths in cloud services, hyperscale data centers, telecom applications and equipment OEM companies. This duplex multimode 50/125 OM4 cable is an ideal choice for 400G Ethernet applications up to 100 meters (at 850 nm). It is also backward compatible with 40 Gb and 100 Gb networks, so you can future-proof your current application for an eventual upgrade to 400 Gb.

Compact CS Connectors Designed for the Latest QSFP-DD Transceivers

The CS ends are 40 percent smaller than standard LC connectors, making them compatible with the latest 400G QSFP-DD transceivers and an excellent solution for high-density network applications. Push/pull tabs allow dense vertical stacking in switches or patch panels where space is at a premium and make the cable easy to install or remove with one hand.

Magenta Jacket Helps Avoid Misidentification That Can Cause Costly Downtime

The OM4-rated cable has a magenta jacket, which is easy to identify quickly in a crowded patch panel or switch and helps prevent the cable from becoming accidentally disconnected. The round low-smoke zero-halogen (LSZH) jacket limits the amount of toxic smoke emitted in case of combustion, making it suitable for poorly ventilated areas.

Specifications

OVERVIEW	
UPC Code	037332258052
Technology	Multimode
Optical Mode	OM4
CONNECTIONS	
CONNECTIONS	

Highlights

- OM4-rated cable recommended for 400 Gb speeds up to 100 m (@ 850 nm)
- CS connectors 40% more dense than standard LC ends for easier cable management
- Smaller-format CS ends designed for next-generation 400G QSFP-DD transceivers
- Backward compatible with 40/100 GbE networks to facilitate future-proofing
- Magenta LSZH jacket allows fast, easy identification in a crowded switch or patch panel

Applications

 Connect 400G fiber Ethernet networks in your cloud service, hyperscale data center or telecom application

Package Includes

 N822C-03M-MG 400Gb Duplex Multimode 50/125 OM4 Fiber Optic Cable, Magenta, 3 m





Product Compliance	RoHS; REACH	
STANDARDS & COMPLIANCE		
Trunk	No	
Breakout	No	
Push/Pull Tabs	Yes	
FEATURES & SPECIFICATIONS		
Insertion Loss	0.20 dB	
Attenuation @ 850NM	3.0 dB/km	
Transmission Distance	100M @ 850NM Wavelength	
Network Compatibility	400 Gbps	
COMMUNICATIONS		
Storage Humidity Range	35% to 65% RH, Non-Condensing	
Operating Humidity Range	5% to 85% RH, Non-Condensing	
Storage Temperature Range	-4° to 140°F (-20° to 60°C)	
Operating Temperature Range	-4° to 140°F (-20° to 60°C)	
ENVIRONMENTAL		
Fiber Cable Length	3M (9.8 ft)	
Minimum Bend Radius	20 mm (Dynamic); 10 mm (Static)	
Cable Length (in.)	118.1	
Cable Length (m)	2.99	
Cable Length (ft.)	9.8	
Number of Fibers	2	
Primary Coating Diameter (microns)	600	
Core Diameter (microns)	50	
Clad Diameter (microns)	125	
Cable Jacket Rating	OFNR	
Cable Jacket Material	LSZH	
Connector Color	White; Aqua	
Cable Jacket Color	Magenta	
PHYSICAL		
Endface Polish	PC	
Side B - Connector 1	CS DUPLEX (MALE)	
Side A - Connector 1	CS DUPLEX (MALE)	



United States

https://tripplite.eaton.com



WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
1000 Eaton Boulevard	© 2024 Eaton. All Rights Reserved.	
Cleveland, OH 44122	Eaton is a registered trademark. All other trademarks	

are the property of their respective owners.