

# SmartRack 1U Digital Temperature Sensor, Blanking Panel, LCD

MODEL NUMBER: SR1UPNLTEMP



1U blanking panel with temperature sensor measures environmental conditions within your rack and displays degrees in F° and C°.

## Features

**1U Blanking Panel with Temperature Sensor Helps Improve Rack Cooling Efficiency** This cold-rolled steel SmartRack® blanking panel with a black powder-coated finish fills 1U of unused space in your EIA-standard 19-inch rack. Not only does this give your rack a sleek, clean look, but it also protects your valuable equipment by improving airflow. By closing off unused rack openings, this blanking panel prevents hot air from recirculating through open spaces. This reduces operating costs, improves performance and provides longer lifespans for your equipment.

**Helps You Precisely Measure Your Rack Temperature, Even High Up** The SR1UPNLTEMP helps you notice hot spots at the top of your rack with the included temperature sensor. The 6-ft. (1.83 m) sensor reaches every crack and crevice within your rack and finds hot spots. The sensor accurately measures the rack temperature within 2°F and 1°C and a range of -58°-302°F and -50°-150°C.

**LCD Indicator Lets You Keep a Close Watch on Environmental Changes** A front-panel LCD lets you monitor the rack temperature in either Fahrenheit or Celsius. One front rocker switch flips between °F and °C. The other turns the SR1UPNLTEMP on and off. The included 12V DC power supply features a 6-ft. (1.83 m) cord and NEMA 1-15P plug that connects to an AC wall outlet, PDU or UPS system.

## Specifications

OVERVIEW	
UPC Code	037332240613
Accessory Type	Temperature Sensor
Accessory Class	Rack Accessories
INPUT	
Nominal Input Voltage(s) Supported	120V AC

## Highlights

- Cold-rolled steel panel fills unused rack space to give enclosure a clean, sleek look
- Protects rack-mount equipment by improving airflow and cooling efficiency
- Included temperature sensor identifies hot spots within the rack up to 6-ft. (1.83 m) away
- Front-panel LCD displays rack temperature in Fahrenheit or Celsius
- Mounts easily into 1U of space in your EIA-standard 19 in. rack enclosure

## Applications

- Close off unused rack spaces to prevent hot air from recirculating around equipment
- Monitor rack temperature at a glance in either Fahrenheit or Celsius

## Package Includes

- SR1UPNLTEMP 1U Blanking Panel
- Temperature sensor
- 12V DC power supply with 6-ft. (1.83 m) cord and NEMA 1-15P plug
- Owner's manual



Powering Business Worldwide



Nominal Input Voltage Description	120V AC 60 Hz
Input Connection Type	NEMA 1-15P
Input Plug Features	NEMA 1-15P
Input Cord Length (ft.)	6
Input Cord Length (m)	1.83
<b>PHYSICAL</b>	
Rack Height	1U
Shipping Dimensions (hwd / in.)	7.48 x 20.35 x 4.21
Shipping Weight (kg)	1.80
Unit Dimensions (hwd / in.)	1.710 x 17.300 x 3.750
Unit Dimensions (hwd / cm)	4.34 x 43.94 x 9.52
Unit Weight (lbs.)	2.460
Unit Weight (kg)	1.12
<b>FEATURES &amp; SPECIFICATIONS</b>	
Sensing Capability	Temperature
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Compliance	RoHS
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	2-year limited warranty

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.