

8-Outlet Surge Protector with 1 USB-A and 1 USB-C (3.9A Shared) - 8 ft. Cord, 2100 Joules, Metal Housing

MODEL NUMBER: TLM88USBC











8-outlet surge protector safeguards your home/office electronics against dangerous surges, spikes and line noise.

Features

8-Outlet Surge Protector with USB Safeguards Your Sensitive Electronics

Ideal for your home, office, retail or industrial workstation, this Protect It!® 8-outlet surge protector features a surge protection rating of 2100 joules to defend your sensitive electronic components against power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLM88USBC protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices

Plug your computer, printer, wireless router, desk lamp and other home/office electronics into eight NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise. Three outlets are separated from the others to allow connection of bulky transformers without blocking adjacent outlets.

2 USB Ports Share 3.9 Amps of Charging Power

This surge protector with one USB-A port and one USB-C port is ideal for keeping your devices at full capacity. The USB ports are available for charging your smartphone, tablet and other mobile devices.

Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better

Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems. This surge protector filters out disruptive line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

Includes the Latest Safety Features

The lighted on/off switch with integrated circuit breaker provides one-touch control over connected equipment. LEDs let you know when your connected devices are properly protected. Each outlet features a built-in safety cover to protect it from dust and other debris when not in use.

Versatile Surge Protector Provides Multiple Installation Options

This surge protector with 8-foot braided AC input cord and NEMA 5-15P plug gives you flexibility in

Highlights

- 8 NEMA 5-15R outlets distribute AC power to connected home/office equipment
- 2100 joules protect your valuable electronics against dangerous surges and spikes
- USB-A and USB-C ports share 3.9A for fast charging of phones and other mobile devices
- 8 ft. braided input cord allows flexibility in placing devices away from wall outlet
- Durable metal housing designed to stand up in harsh environments, such as warehouses

Applications

- Protect computers, peripherals, home theater equipment and other valuable electronics against AC power surges and spikes
- Filter potentially damaging line noise to improve connected equipment's performance and lifespan
- Safeguard valuable data against damage stemming from unexpected surges
- Charge smartphones, tablets or other USB devices via USB ports

Package Includes

- TLM88USBC Protect It! 8-Outlet Surge Protector, Black Metal Housing
- Owner's manual



placing the unit away from the nearest wall outlet. Keyhole slots incorporated into the bottom panel provide convenient wall or desk mounting options for the black metal housing.

Specifications

OVERVIEW		
UPC Code	037332260055	
Product Type	Surge Protector	
Charging Form Factor	Strip	
Device Compatibility	Phone; Tablet; Amazon Kindle	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Cord Gauge Type	14 gauge; SJT	
Input Cord Gauge (AWG)	14	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	35500	
Input Plug Type	NEMA 5-15P	
Input Cord Details	SJT	
Input Cord Length (ft.)	8	
Right-Angle Plug	No	
Input Cord Length (m)	2.44	
Integrated Cord Clip	No	
ОИТРИТ		
Frequency Compatibility	50 / 60 Hz	
Output Receptacles	(8) 5-15R	
Circuit Breaker (amps)	15	
Overload Protection	15A resettable illuminated combo switch / circuit breaker	
Transformer Accommodation	(1) Yes	
Right-Angle Outlets	Yes	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	Yes	
Switches	Combination AC circuit breaker and 2 position red illuminated on/off power switch	
Diagnostic LED Details	1x Green Protected and 1x Red Grounded	



USB A (FEMALE); (1) USB C (FEMALE) 3.9A 00 Ins cludes full normal mode (H-N) and common mode (N-G / H-G) line suppression N, L-G, N-G, 500, 500, 500 s	
USB A (FEMALE); (1) USB C (FEMALE) 3.9A 00 Ins cludes full normal mode (H-N) and common mode (N-G / H-G) line suppression N, L-G, N-G, 500, 500, 500 s	
USB A (FEMALE); (1) USB C (FEMALE) 3.9A 00 Ins cludes full normal mode (H-N) and common mode (N-G / H-G) line suppression N, L-G, N-G, 500, 500, 500 s	
USB A (FEMALE); (1) USB C (FEMALE) 3.9A 00 Ins cludes full normal mode (H-N) and common mode (N-G / H-G) line suppression N, L-G, N-G, 500, 500, 500 s	
3.9A 00 I ns cludes full normal mode (H-N) and common mode (N-G / H-G) line suppression N, L-G, N-G, 500, 500, 500 s	
00 I ns cludes full normal mode (H-N) and common mode (N-G / H-G) line suppression N, L-G, N-G, 500, 500, 500 s	
00 I ns cludes full normal mode (H-N) and common mode (N-G / H-G) line suppression N, L-G, N-G, 500, 500, 500 s	
ludes full normal mode (H-N) and common mode (N-G / H-G) line suppression N, L-G, N-G, 500, 500, 500 s	
ludes full normal mode (H-N) and common mode (N-G / H-G) line suppression N, L-G, N-G, 500, 500, 500 s	
cludes full normal mode (H-N) and common mode (N-G / H-G) line suppression N, L-G, N-G, 500, 500, 500 s	
N, L-G, N-G, 500, 500, 500 s	
S	
S	
PHYSICAL	
etal	
ack; Gray Braided Cord	
ack; Silver	
)	
ack	
.600 x 3.700 x 1.400	
.92 x 9.4 x 3.56	
30	
32	
FEATURES & SPECIFICATIONS	
10 march 10	



STANDARDS & COMPLIANCE		
Product Certifications	CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); UL 1449; UL 1363	
Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$25,000 Ultimate Lifetime Insurance	



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.