



# Heavy-Duty USB-A to USB-C Cable, USB 2.0, UHMWPE and Aramid Fibers, (M/M), Gray, 6 ft. (1.83 m)

### MODEL NUMBER: U038-006-GY-MAX











Durable USB cable connects a smartphone or other USB-C device to the USB-A port on your computer, wall charger or car charger.

#### **Features**

Heavily Reinforced USB 2.0 Cable Charges and Syncs Your Phone or Other USB-C DeviceThis heavy-duty USB sync/charge cable (M/M) connects your smartphone, tablet, MacBook, Ultrabook, Chromebook or other USB-C device to the USB-A port on a computer, car charger or wall charger. It allows you to charge and power your USB-C device, while simultaneously synching and transferring data at USB 2.0 data transfer speeds up to 480 Mbps. The cable is backward compatible with previous USB generations, allowing you to use it with older equipment.

Constructed Using UHMWPE and Bulletproof Aramid Fiber Designed to LastCharging cables used with mobile devices are often pulled, strained and generally abused, sometimes to the point of failure. To counter the stress of daily abuse, the super-robust U038-006-GY-MAX is constructed using UHMWPE and Aramid fiber to reinforce the conductors inside the cable. The double-braided nylon jacket helps maintain top performance and long life, while the enhanced UHMWPE and Aramid protection stands up to the strain of rigorous and frequent use. Integral strain relief gives the cable extra flexibility, reduces stress, and helps the cable move freely without cracking or breaking loose from the connector.

Reversible USB-C Connector Attaches in Either DirectionUnlike traditional USB cables that connect in only one direction, the reversible USB-C male connector plugs into a USB-C or Thunderbolt 3 port in either direction for a fumble-free connection every time.

#### **Highlights**

- Engineered using UHMWPE and Aramid fiber to stand up to frequent and rigorous use
- Extra-strong cable construction helps prevent fraying and loose cable connectors
- Supports USB 2.0 speeds up to 480 Mbps to ensure efficient charging and data transfers
- Integral strain relief helps cable move freely without stress or cracking
- Reversible USB-C plug connects in either direction for immediate no-fuss use

#### **Applications**

- Charge and sync your MacBook, Chromebook or other USB-C device from a USB computer or wall charger up to 6 ft. away
- Transfer data between an external hard drive and your USB-C notebook or computer
- Replace a cable that became frayed or inoperable due to frequent use

#### **System Requirements**

- Device or charger with USB-A port
- Device with USB-C port

## **Package Includes**

 U038-006-GY-MAX Heavy-Duty USB-A to USB-C Cable (M/M), Gray, 6 ft. (1.8 m)

# **Specifications**

| OVERVIEW   |                      |
|------------|----------------------|
| UPC Code   | 037332241337         |
| Technology | USB 2.0 (High Speed) |
| Cable Type | Passive              |





| INPUT                                    |                              |
|------------------------------------------|------------------------------|
| Maximum Input Amps                       | 3                            |
| POWER                                    |                              |
| USB Power Delivery (PD) Charging Support | No                           |
| CONNECTIONS                              |                              |
| Side A - Connector 1                     | USB A (MALE)                 |
| Side B - Connector 1                     | USB C (MALE)                 |
| Connector Plating                        | Nickel                       |
| Contact Plating                          | Gold                         |
| Connector Style                          | Straight                     |
| CHARGING                                 |                              |
| Total Charging Watts                     | 15                           |
| PHYSICAL                                 |                              |
| Material of Construction                 | PVC, UHMWPE, Aramid          |
| Cable Jacket Color                       | Black                        |
| Cable Jacket Material                    | PVC                          |
| Cable Jacket Rating                      | VW-1                         |
| Cable Outer Diameter (OD)                | 3.8 mm                       |
| Cable Length (ft.)                       | 6                            |
| Cable Length (m)                         | 1.83                         |
| Cable Length (in.)                       | 72                           |
| Cable Length (cm)                        | 182.9                        |
| Shipping Dimensions (hwd / in.)          | 9.00 x 7.00 x 0.50           |
| Shipping Weight (kg)                     | 0.01                         |
| Unit Dimensions (hwd / in.)              | 0.000 x 0.000 x 0.000        |
| Unit Packaging Type                      | Polybag                      |
| ENVIRONMENTAL                            |                              |
| Operating Temperature Range              | -4° to 140°F (-20° to 60°C)  |
| Storage Temperature Range                | -4° to 176°F (-20° to 80°C)  |
| Relative Humidity                        | 0% to 90% RH, Non-Condensing |
| Operating Humidity Range                 | 0% to 90% RH, Non-Condensing |
| Storage Humidity Range                   | 0% to 90% RH, Non-Condensing |





| Power Provided to Connected Device(s)  | 15W (5V/3A)               |  |
|----------------------------------------|---------------------------|--|
| FEATURES & SPECIFICATIONS              |                           |  |
| USB Specification                      | USB 2.0 (up to 480 Mbps)  |  |
| Data Transfer Rate                     | 480 Mbps                  |  |
| Angled Plug                            | No                        |  |
| STANDARDS & COMPLIANCE                 |                           |  |
| Product Compliance                     | RoHS; CE (Europe); REACH  |  |
| WARRANTY & SUPPORT                     |                           |  |
| Product Warranty Period<br>(Worldwide) | Lifetime limited warranty |  |

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.