



# USB-C to USB-A Adapter (M/F), USB 3.2 Gen 1 (5 Gbps), USB-IF Certified, Thunderbolt 3 Compatible, 6-in. (15.24 cm)

MODEL NUMBER: U428-C6N-F











USB Type-C to Type-A adapter connects an existing USB cable or device to your MacBook or Chromebook's USB-C or Thunderbolt 3 port.

#### **Features**

USB Type-C to USB Type-A Adapter Connects an Existing USB Device to Your USB-C LaptopThis six-inch USB-C 3.1 to USB-A cable allows you to connect USB devices to your smartphone, tablet, laptop, MacBook, Chromebook or Ultrabook's USB-C or Thunderbolt 3 port. USB wall chargers, hard drives, memory sticks, printers and other peripherals with USB-A ports will be able to communicate with your computer or other USB-C mobile device.

PD Charging Cable Charges Devices and Transfers Data at Fast USB 3.1 Gen 1 SpeedsThe USB-C to USB-A cable supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps, which is 10 times faster than USB 2.0. The Power Delivery cable also provides power output up to 3 amps (60 watts), which is more than sufficient for charging, syncing and powering compatible devices. The cable is backward compatible with previous USB generations, allowing you to use it with older USB 3.0, USB 2.0 or USB 1.1 equipment.

Reversible USB-C Connector Attaches in Either DirectionUnlike traditional USB cables that connect in only one direction, the reversible USB-C male connector plugs into a USB-C or Thunderbolt 3 port in either direction for a fumble-free connection every time.

**USB-IF Certification Ensures Rigorous Testing and Top-of-the-Line Performance**This USB Type-C to USB Type-A cable meets the high standards of USB-IF (USB Implementers Forum, Inc.), a non-profit organization consisting of companies that developed the USB specification. Receiving USB-IF certification means the U428-C6N-F meets the industry's highest environmental, mechanical and electrical standards. It operates with your USB peripherals, adapters and cables with top efficiency and safety.

### **Highlights**

- Certified by USB-IF to ensure highest-grade construction and performance
- Supports USB 3.1 Gen 1 speeds up to 5 Gbps to ensure fast data transfers
- Power Delivery cable provides 3A (60W) power output for charging mobile devices
- Reversible USB-C plug connects in either direction for immediate no-fuss use
- USB-C to USB-A adapter cable compatible with USB-A, USB-C and Thunderbolt 3 devices

### **Applications**

- Charge and sync a USB-C or Thunderbolt 3 mobile device from a USB-A wall charger
- Connect a printer or scanner to the USB-C port on your computer or laptop
- Transfer data between an external hard drive or flash drive and your computer or laptop
- Connect your computer or laptop to a docking station or hub

#### **System Requirements**

- Device with a USB-C or Thunderbolt 3 port (USB 3.1 Gen 1 compatibility required to achieve USB 3.1 Gen 1 speeds)
- Device with a USB-A port

### **Package Includes**

 U428-C6N-F USB Type-C to USB Type-A Adapter Cable, M/F, USB-IF, 6 in.

## **Specifications**

| OVERVIEW   |                      |
|------------|----------------------|
| UPC Code   | 037332218087         |
| Technology | Thunderbolt; USB 3.x |





| Cable Type                          | Passive                             |  |
|-------------------------------------|-------------------------------------|--|
| CONNECTIONS                         |                                     |  |
| Side A - Connector 1                | USB C (MALE)                        |  |
| Side B - Connector 1                | USB 3.0 A (FEMALE)                  |  |
| Connector Plating                   | Nickel                              |  |
| Contact Plating                     | Gold                                |  |
| Connector Style                     | Straight                            |  |
| Connector Style                     | Straight                            |  |
| PHYSICAL                            |                                     |  |
| Material of Construction            | PVC                                 |  |
| Cable Jacket Color                  | Black                               |  |
| Cable Jacket Rating                 | VW-1                                |  |
| Cable Outer Diameter (OD)           | 4.5 mm                              |  |
| Cable Length (ft.)                  | 0.5                                 |  |
| Cable Length (m)                    | 0.15                                |  |
| Cable Length (in.)                  | 6                                   |  |
| Shipping Dimensions (hwd / in.)     | 9.00 x 7.00 x 0.50                  |  |
| Shipping Dimensions (hwd / cm)      | 22.86 x 17.78 x 1.27                |  |
| Shipping Weight (lbs.)              | 0.04                                |  |
| Shipping Weight (kg)                | 0.02                                |  |
| Unit Packaging Type                 | Polybag                             |  |
| ENVIRONMENTAL                       |                                     |  |
| Operating Temperature Range         | 14° to 140°F (-10° to 60°C)         |  |
| Storage Temperature Range           | -4° to 158°F (-20° to 70°C)         |  |
| Relative Humidity                   | 10% to 85% RH, Non-Condensing       |  |
| FEATURES & SPECIFICATIONS           |                                     |  |
| USB Specification                   | USB 3.1 Gen 1 (up to 5 Gbps)        |  |
| COL Oppositionation                 |                                     |  |
| STANDARDS & COMPLIANCE              |                                     |  |
| Product Certifications              | USB-IF                              |  |
| Product Compliance                  | RoHS; CE (Europe); REACH; FCC (USA) |  |
| WARRANTY & SUPPORT                  |                                     |  |
| Product Warranty Period (Worldwide) | Lifetime limited warranty           |  |





1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.