

USB-C to DisplayPort Active Adapter Cable (M/M), 4K 60 Hz, 3 ft. (0.9 m)

MODEL NUMBER: U444-003-DP











USB-C to DisplayPort adapter connects your DP monitor to the USB-C or Thunderbolt 3 port on your Chromebook or MacBook.

Features

Connects a DisplayPort Display to Your USB-C or Thunderbolt 3 DeviceThis USB-C to DisplayPort 4K cable helps you transmit digital audio and 4K video from your tablet, laptop, Chromebook, MacBook, smartphone or PC to a DisplayPort-enabled monitor or projector. It's ideal for giving video presentations in conference rooms and classrooms, editing multiple documents on a larger screen, or streaming video for digital signage in crystal-clear 4K.

Supports USB DisplayPort Alternate Mode for Transmitting Audio/Video SignalsWith a source device that also supports USB DisplayPort Alt Mode, you can extend video from your primary display to another, duplicate the same video on both displays, or change the second display to your primary.

Transmits Crystal-Clear 4K Video and Digital AudioThis three-foot cable supports Ultra High Definition (UHD) video resolutions up to 3840 x 2160 (4K x 2K) at 60 Hz, 36-bit Deep Color (12 bits per channel) and per-lane transfer rates of 5.4 Gbps (HBR2), 2.7 Gbps (HBR) and 1.62 Gbps (RBR). It also supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps. The cable is backward compatible with non-4K displays, so you can use a 1080p monitor if one is available.

Built-In USB-C Cable Connects in Either DirectionConnect the reversible USB-C plug to your source device's USB-C or Thunderbolt 3 port. The fumble-free USB-C plug connects in either direction to ensure fast, easy connection every time.

Premium Construction for Premium PerformanceFoil and braid shielding delivers reliable, error-free signal quality and protection from EMI/RFI line noise that can distort or destroy data. Molded gold-plated connectors with corrosion-resistant gold-plated contacts provide maximum conductivity and minimize data loss. Integral strain relief reduces stress and helps the cable and connectors move freely without cracking.

Ready to Use Right Out of the PackageThe plug-and-play USB-C to DisplayPort adapter requires no software, drivers or external power and works with both Windows and Mac operating systems. Just plug the USB-C end into your computer's USB-C or Thunderbolt 3 port, and plug the DisplayPort end into the display's input port for immediate satisfaction. The three-foot cable fits easily into a briefcase or laptop bag for connecting on the go.

3-Year Warranty and Environmentally Responsible DesignThe U444-003-DP comes with a 3-year

Highlights

- Transmits video signals from sources supporting USB DisplayPort Alt Mode
- Delivers UHD picture quality at resolutions up to 3840 x 2160 (4K x 2K) @ 60 Hz
- Supports USB 3.1 Gen 1 speeds up to 5 Gbps to ensure fast data transfers
- Reversible USB-C plug connects in either direction for immediate no-fuss use
- Easy installation with plug-andplay operation—no software required
- Note: This cable is unidirectional. Will only work from a USB-C port to DisplayPort

Applications

- Play 4K video from your laptop, Chromebook or MacBook on a large-screen monitor
- Give a video presentation at a meeting, training session, conference or trade show
- Multitask in two or more applications on multiple displays
- Add a second monitor and make it your primary monitor
- Edit large documents on two different monitors

System Requirements

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate Mode
- Display device with DisplayPort input

Package Includes

U444-003-DP USB-C to DisplayPort Cable, 4K @ 60Hz, Thunderbolt 3, 3 ft.



warranty. It's manufactured in compliance with strict RoHS specifications, reflecting commitment to environmental responsibility.

Locking DP Connector Helps Prevent Accidental Disconnection and Expensive DowntimeHaving a cable come loose accidentally can mean costly and time-consuming signal loss. The locking DisplayPort connector helps you avoid such danger, protecting your audio/video transmission by maintaining a secure link without failure. The locking cable is also invaluable when moving equipment in a rack or removing equipment from tight areas, ensuring the cord always stays connected.

Specifications

OVERVIEW		
UPC Code	037332210371	
Product Type	Active Cable	
Technology	DisplayPort	
Cable Type	Active	
VIDEO		
Max Supported Video Resolution	3840 x 2160 (4K) @ 60Hz	
HDR Support	Yes	
INPUT		
Bus Powered	Yes	
Product Length (in.)	36	
Product Length (cm.)	91.44	
Product Length (ft.)	3	
Product Length (m.)	0.91	
BATTERY		
Battery Charging (5V/1.5A Port)	No	
POWER		
Power Consumption (Watts)	0.60	
PHYSICAL		
Color	Black	
Material of Construction	PVC, ABS	
Cable Jacket Color	Black	
Cable Jacket Rating	VW-1	
Cable Length (ft.)	3	



Cable Length (m) Cable Length (in.) Cable Length (in.) Shipping Dimensions (hwd / in.) Shipping Weight (lbs.) Unit Dimensions (hwd / in.) Unit Packaging Type Unit Weight (lbs.) Unit Weight (lbs.) Unit Weight (kg) Polybag Unit Weight (kg) Corrections Storage Temperature Range Storage Temperature Range BTUS Connector Humidity Range Storage Humidity Range Storage Humidity Range Storage Temperature Range Storage Temperature Range BTUS CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 Connector Plating Gold FEATURES & SPECIFICATIONS USB Specification USB 3.0 (up to 5 of the content of th		
Shipping Dimensions (hwd / in.) Shipping Weight (lbs.) Unit Dimensions (hwd / in.) Unit Packaging Type Unit Weight (lbs.) Unit Weight (lbs.) Unit Weight (kg) ENVIRONMENTAL Operating Temperature Range Storage Temperature Range BTUs 2.1 BTU/Hr Operating Humidity Range Storage Humidity Range CONNECTIONS Side A - Connector 1 Side B - Connector 1 USB C (MALE) Side B - Connector 1 Connector Plating FEATURES & SPECIFICATIONS USB Specification USB 3.0 (up to 5.0 kg and bus an		
Shipping Weight (lbs.) Unit Dimensions (hwd / in.) Unit Packaging Type Polybag Unit Weight (lbs.) Unit Weight (kg) ENVIRONMENTAL Operating Temperature Range Storage Temperature Range BTUs 2.1 BTU/Hr Operating Humidity Range 10% to 85% RH, N Storage Humidity Range Side A - Connector 1 USB C (MALE) Side B - Connector 1 Connector Plating Gold FEATURES & SPECIFICATIONS USB Specification USB 3.0 (up to 5.0 kg and more support) Auto MDIX Support No Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.3		
Unit Dimensions (hwd / in.) Unit Packaging Type Polybag Unit Weight (lbs.) Unit Weight (kg) ENVIRONMENTAL Operating Temperature Range Storage Temperature Range BTUs CONNECTIONS Side A - Connector 1 Side B - Connector 1 Connector Plating USB Specification USB Specification USB Specification USB Support No Auto MDIX Support No Remote Wakeup Support No Displayport Specification USB Connector 1 No Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification U.16 U.16 U.17 U.17 U.17 U.17 U.17 U.17 U.17 U.17		
Unit Packaging Type Unit Weight (lbs.) Unit Weight (kg) ENVIRONMENTAL Operating Temperature Range Storage Temperature Range BTUs Operating Humidity Range 10% to 85% RH, No Storage Humidity Range 5% to 90% RH, No CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 Connector Plating Gold FEATURES & SPECIFICATIONS USB Specification USB 3.0 (up to 5.0 IP68 Rated No UASP Support No Auto MDIX Support No Suspend Mode Support No Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.3		
Unit Weight (lbs.) Unit Weight (kg) 0.07 ENVIRONMENTAL Operating Temperature Range Storage Temperature Range BTUs 2.1 BTU/Hr Operating Humidity Range 10% to 85% RH, N Storage Humidity Range 5% to 90% RH, No CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 Connector Plating Gold FEATURES & SPECIFICATIONS USB Specification USB 3.0 (up to 5 of the plant	000	
ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to Storage Temperature Range 14° to 158°F (-10° to	Polybag	
ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to Storage Temperature Range 14° to 158°F (-10° to		
Operating Temperature Range Storage Temperature Range BTUS 2.1 BTU/Hr Operating Humidity Range Storage Humidity Range Temperature Range Storage Humidity Range Storage Humidity Range Temperature Range Storage Humidity Range Storage Humidity Range Storage Humidity Range Temperature Range Storage Humidity Range Storage Range Storage Humidity Range Storage Range Storage Humidity Range Storag		
Storage Temperature Range BTUS 2.1 BTU/Hr Operating Humidity Range 10% to 85% RH, N Storage Humidity Range 5% to 90% RH, No CONNECTIONS Side A - Connector 1 Side B - Connector 1 Connector Plating Gold FEATURES & SPECIFICATIONS USB Specification USB 3.0 (up to 5 0 IP68 Rated No IP20 Rated VASP Support Auto MDIX Support Auto MDIX Support No Suspend Mode Support No Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 10% to 158°F (-10° 2.1 BTU/Hr 10% to 85% RH, No USB C (MALE) DISPLAYPORT (No No No No 1.2 HDCP Specification 1.3		
BTUS 2.1 BTU/Hr Operating Humidity Range Storage Humidity Range 5% to 90% RH, No CONNECTIONS Side A - Connector 1 Side B - Connector 1 Connector Plating Gold FEATURES & SPECIFICATIONS USB Specification USB 3.0 (up to 5 of the second support of the seco	9.45°C)	
Operating Humidity Range 10% to 85% RH, No Storage Humidity Range 5% to 90% RH, No CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 DISPLAYPORT (No Connector Plating Gold FEATURES & SPECIFICATIONS USB Specification USB 3.0 (up to 5 constant) IP68 Rated No IP20 Rated No UASP Support No Auto MDIX Support No Suspend Mode Support No Suspend Mode Support No Displayport Specification 1.2 HDCP Specification 1.3	to 70°C)	
Storage Humidity Range 5% to 90% RH, No CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 DISPLAYPORT (No Connector Plating Gold FEATURES & SPECIFICATIONS USB Specification USB 3.0 (up to 5 constant) IP68 Rated No IP20 Rated No UASP Support No Auto MDIX Support No Full Duplex Support No Suspend Mode Support No Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.3		
CONNECTIONS Side A - Connector 1 USB C (MALE) Side B - Connector 1 DISPLAYPORT (Not on the connector Plating Gold FEATURES & SPECIFICATIONS USB Specification USB 3.0 (up to 5 constant) IP68 Rated Not on the connector Not on the connector Plating Gold IP20 Rated Not on the connector Not on the connector Plating Gold IP68 Rated Not on the connector Not on the	Non-Condensing	
Side A - Connector 1 Side B - Connector 1 Connector Plating FEATURES & SPECIFICATIONS USB Specification USB 3.0 (up to 5 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	on-Condensing	
Side B - Connector 1 DISPLAYPORT (Not Connector Plating) Gold FEATURES & SPECIFICATIONS USB Specification USB 3.0 (up to 5 constitution) No USB 3.0 (up to 5 constit		
Connector Plating Gold FEATURES & SPECIFICATIONS USB Specification USB 3.0 (up to 5 0) IP68 Rated No IP20 Rated No UASP Support No Auto MDIX Support No Full Duplex Support No Suspend Mode Support No Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.3		
FEATURES & SPECIFICATIONS USB Specification USB 3.0 (up to 5.0 lp68 Rated No IP20 Rated No UASP Support No Auto MDIX Support No Full Duplex Support No Suspend Mode Support No Remote Wakeup Support Displayport Specification 1.2 HDCP Specification 1.3	MALE)	
USB Specification IP68 Rated IP20 Rated IP20 Rated No UASP Support No Auto MDIX Support No Full Duplex Support No Suspend Mode Support No Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.3		
IP68 Rated No IP20 Rated No UASP Support No Auto MDIX Support No Full Duplex Support No Suspend Mode Support No Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.3		
IP20 Rated No UASP Support No Auto MDIX Support No Full Duplex Support No Suspend Mode Support No Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.3	Gbps); USB 3.1 Gen 1 (up to 5 Gbps)	
UASP Support No Auto MDIX Support No Full Duplex Support No Suspend Mode Support No Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.3		
Auto MDIX Support No Full Duplex Support No Suspend Mode Support No Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.3		
Full Duplex Support No Suspend Mode Support No Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.3		
Suspend Mode Support No Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.3		
Remote Wakeup Support No Displayport Specification 1.2 HDCP Specification 1.3		
Displayport Specification 1.2 HDCP Specification 1.3		
HDCP Specification 1.3		
Driver Required No		
Driver Required 140		
STANDARDS & COMPLIANCE		
Product Compliance CE (Europe); FCC	(USA); REACH; RoHS; UKCA; WEEE	



WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	3-year limited warranty



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.